Quick4Plus' Standard

Chambers

The Quick4 Plus Standard Chamber offers maximum strength through its two center structural columns. This chamber can be installed in a 36-inch-wide trench. Like the original line of Quick4 chambers, it offers advanced contouring capability with its Contour Swivel Connection[™] which permits turns up to 15-degrees, right or left. It is also available in four-foot lengths to provide optimal installation flexibility. The Quick4 Plus All-in-One 12 Endcap, and the Quick4 Periscope are available with this chamber, providing increased flexibility in system configurations.


Benefits

- Two center structural columns offer increased stability and superior strength
- Advanced contouring connections
- · Latching mechanism allows for quick installation
- Four-foot chamber lengths are easy to handle and install
- Supports wheel loads of 16,000 lbs/axle with 12" of cover


Quick4 Plus All-in-One Endcap Benefits

- May be used at the end of chamber row for an inlet/outlet or can be installed mid-trench
- Mid-trench connection feature allows construction of chamber rows with center feed, as an alternative to inletting at the ends of chamber rows
- Center-feed connection allows for easy installation of serial distribution systems
- · Pipe connection options include sides, ends or top


Quick4 Plus Standard Chamber




Quick4 Plus All-in-One Periscope



Quick4 Plus All-in-One 12 Endcap







Quick4 Plus Standard with All-in-One Endcap

Quick4 Plus All-in-One Periscope

- Allows for raised invert installations
- 180° directional inletting
- 12" raised invert is ideal for serial applications

Quick4 Plus Standard Specifications	
Size	34"W x 53"L x 12"H (864 mm x 1346 mm x 305 mm)
Effective Length	48" (1219 mm)
Louver Height	8" (203 mm)
Storage Capacity	547 gal (178 L)
Invert Height	0.6" (15 mm), 5.3" (135 mm), 8.0" (203 mm), 12.7" (323 mm)

Contact Infiltrator's Technical Services Department for assistance at 1-800-221-4436 or info@infiltratorwater.com



infiltratorwater.com • (800) 221-4436