



Community Wastewater Treatment System Recharges Groundwater Supplies and Minimizes Saltwater Intrusion

Project Name

Los Osos, Calif. Community Wastewater Treatment System

System Specifications

1.6 MGD collection, conveyance, treatment and water reuse

Infiltrator Products Used

20,000 linear feet of Infiltrator Chambers

Installation Date

Summer 2013

Designer

CDM Smith
Walnut Creek, Calif.

Installing Contractor

WA Rasic Construction
Long Beach, Calif.

Owner

San Luis Obispo County, Calif.



The coastal community of Los Osos, California had for generations met their wastewater needs with onsite wastewater treatment systems that were now outdated. As urban density increased, code-compliant systems could not be designed to fit the small lots. Additionally, the coastal, agricultural community was experiencing saltwater intrusion as groundwater was pumped to meet demand and hence saltwater began to intrude further inland. The Regional Water Quality Control Board declared a prohibition zone and a building moratorium.

Challenges

Initial studies revealed that the discharge for a centralized wastewater treatment system would have to be an ocean outfall and raised concerns that saltwater intrusion would be increased. A decentralized solution that includes final discharge to a community drainfield, recharge the groundwater supplies, minimize saltwater intrusion, and serve the community for the future was ultimately selected.

System Details

The completed large community treatment system has a capacity of a capacity of 1.6 MGD and includes collection, conveyance, treatment, and recycled water reuse. The system's conventional gravity collection system includes pump stations to deliver effluent to the wastewater treatment plant, which uses membrane treatment technology to remove the nitrogen. Treated effluent is pumped up a hillside where the large subsurface disposal and recharge system is located under a five-acre field that will remain as open space.

The disposal and recharge system utilizes approximately 20,000 linear feet of Infiltrator chambers installed in a series of trenches that offer enhanced infiltrative surface area to return the treated effluent back into the soil to replenish groundwater supplies.

Result

Specifying Infiltrator chambers resulted in cost efficiencies including installation and labor cost savings due to the ease of the lightweight chamber installation as compared to stand-alone stone trenches.



www.infiltratorwater.com

800.221.4436

info@infiltratorwater.com

IWTCS522014